## DiaSafe Fall Protection System mod. GLIDE

Ballasted Fall Protection System, which ensures unhindered movement along the lifeline

## #130100 Technical Data Sheet

Green up the roof!

|   | class A an<br>gliders ass<br>Installed w<br>steel cable<br>componen<br>laminated<br>with height<br>material in<br>whole balla<br>(316) stain<br>and salt ai<br>fully-function | d ballasted safety system against fall, standard EN 795:2012,<br>d C certified, as fall arrest or fall restraint system. The<br>sure unhindered, and continuous movement along the lifeline.<br>ithout penetrating the waterproof membrane, with stainless<br>e (8 mm) followed by the construction documents. System<br>ts are "Amoeba"-shaped damping plate, with a fibreglass<br>cone and laminated ballasting mat, in signal-green colour,<br>t-marking lines for assisting measurement of ballast<br>dry conditions at 80 kg/m2 distributed evenly over the<br>asting mat surface. All metal accessories made out of 1.4404<br>less steel, resistant to acid rain in industrial regions<br>r in coastal regions. The system supplied as<br>onal device ready for immediate professional installation<br>to the approved implementation plan and laid out using<br>provided by the manufacturer.<br><b>DiaSafe Fall Protection System mod. GLIDE</b> |
|---|---|--|
| Max. roof slope   |   | 5°   |
| Integrated safety damping mat   | m   | 3×3  |
| Min. loading weight/post<br>in case of 3×3 m                            | kg/post   | 720/1800   |
| bailasting mat<br>Min. bailasting weight in<br>case of 3×3 m ballasting | kg/m²   | 80/200   |
| mat<br>Max. number of users   |   | See installation documents   |
| Distance between posts  | m   | 1,5-8  |
| Max. tensile stress on the roof insulation, in case                     | N/mm2   | 0.00155  |
| of standard<br>Maximum deflection of the<br>system in case of fall      | m   | 2,38   |
| Min. distance from the edge of roof                                     | m   | 1,5  |
| Cable properties  |   | 8 mm Stainless steel 1.4404 (316)  |
| Frequency of system<br>inspection                                       |   | annualy<br>Roviewod: 2015.02.05.10:20:22   |

Reviewed: 2015-02-05 10:39:32

Specifications are subject to change without notice.

