

FLG-50 Fix Single System


Fall arrest system for roofs up to a 5% slope with stainless steel anchor posts that are not mechanically fixed to the building structure.

#130215



Technical Data Sheet

■ Green up the roof!

| | | |
|---|-------------|---|
|  | | |
| | Dim. | FLG-50 Fix Single System |
| Width | m | 5 (Force distributing fabric: FGT-180) |
| Lenght | mm | 1200 (Damping plates: FGS-1.0) |
| Thickness | mm | 10 (Damping plates: FGS-1.0) |
| Number of individuals | | 1 |
| Material | | Stainless steel (Single post: FH-30) |
| Water permeability | lxm²xs | 105 (Force distributing fabric: FGT-180) |
| Tensile strength warp | KN/m | 11,5 (Force distributing fabric: FGT-180) |
| Tensile strength weft | KN/m | 11,5 (Force distributing fabric: FGT-180) |
| Length | m | 8 (Force distributing fabric: FGT-180) |
| Diameter | cm | ø25 (Single post: FH-30 Supporting area) |
| Height | cm | 30 (Single post: FH-30) |

Reviewed: 2010-10-15 09:11:29

Specifications are subject to change without notice.

DIADEM USA, Inc.

8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062
 Email: info@diademusa.com; Web: www.diademusa.com