

FLG-30 Fix Single System

130213

Fall arrest system for roofs up to a 5% slope with stainless steel anchor posts that are not mechanically fastened.

KEY FEATURES

- Simple construction
- No need to break through roof insulation
- No "heat bridge" developing
- Able to take on forces /stress from any direction
- Integrated with lightning conductor system



APPLICATION

Can be built in on any green roof with a slope of 5% the most, or on loaded flat roofs. Growth medium as load or other filled weight is needed 80 kg/ m.



SPECIFICATION

TECHNICAL DATA

Width: (mm)	1000 (Damping plates: FGS-1.0)
Length: (mm)	1200 (Damping plates: FGS-1.0)
Thickness: (mm)	10 (Damping plates: FGS-1.0)
Length: (m)	8 (Force distributing fabric: FGT-180)
Width: (m)	5 (Force distributing fabric: FGT-180)
Height: (cm)	30 (Single post: FH-30)
Water permeability: (l×m²×s)	105 (Force distributing fabric: FGT-180)
Tensile strength weft: (KN/m)	11,5 (Force distributing fabric: FGT-180)
Tensile strength warp: (KN/m)	11,5 (Force distributing fabric: FGT-180)
Diameter: (cm)	ø25 (Single post: FH-30 Supporting area)
Number of individuals:	1

Reviewed: 2010-10-14 15:03:32



DIADEM USA, Inc.
8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062
info@diademusa.com • www.diademusa.com



Green Up the Roof!