


DiaSafe-Single-System "Solo"

Fall protection system with single anchoring point
#130097



Manual

■ Green up the roof!



Application:

For ensuring the safety of one ("Solo") or two ("Duo") people working at height on flat roofs with up to 5° incline. The anchor point is the circular opening on the top of the stainless steel post and the user attaches the carabiner of the personal safety rope system directly to this post. Care must be taken during use to ensure that the rope is always taut, as detailed in the user manual.

Installation instructions:

The installation must be completed by certified DiaSafe® installers, and only they are authorised to issue the operating licence. Steps of installation: 1. After installing the filter or protection geotextile layer, place the system on top in the exact position set out in the producer's plan 2. Unfold the damping mat without creases (standard unfolded size: 3x3 m). 3. Spread the ballasting weight evenly, make sure the weight is sufficient for the surface area of the damping mat. 4. Finally, the certified installer completes and attaches the control label as well as the circular validation sticker onto the cone. 5. Register the system at diasafe.com by using the serial number.

Installation Tools:

Measuring tape

Installation Photos:

Reviewed: 2014-04-30 08:54:44

DIADEM USA, Inc.

8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062
Email: info@diademusa.com; Web: www.diademusa.com