

# BGS-Service


DRS-Standard is a self stabilized safety railing with ballast for roof installation without penetrating the membranes.

#710903



## Technical Data Sheet

■ Green up the roof!

	<p>The DRS-Standard is a safety railing system which complies with the requirements of building codes without penetrating the roofing membranes. The railing system assembly includes the following components: Steel Fencing Panels with top rail and vertical rods; Steel Ballast Trays; and Steel Support feet. Together they make up the railing system Frame which when combined with ballast creates the safety barrier. Based on the safety or the design requirement, the ballast may be provided with any of the following products: Plastic Planting Containers filled with growing media and planting material; or Concrete Slabs; or Concrete Curbs; or combinations of the three.</p>	
	Dim.	BGS-Service
Height of barrier	inch	43"
Height of container	inch	13-1/2"
Width of Container	inch	19-11/16"
Width of section	inch	39"
Lenght of Container	inch	19-11/16"
Lenght of Section	inch	39"
Material of Container		Polystyrene
Material of the frame		Hot dip galvanized / Stainless steel
Color	RAL	on-demand
Material requirement	ft / ft	1,00
Installation standard	hr / ft	0,30

Reviewed: 2012-10-18 08:56:19

Specifications are subject to change without notice.

### DIADEM USA, Inc.

8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062  
 Email: info@diademusa.com; Web: www.diademusa.com