

# FLG-50 line system

130082

## KEY FEATURES

- Simple construction
- No need to break through roof insulation
- No "heat bridge" developing
- Able to take on forces /stress from any direction
- Integrated with lightning conductor system



## APPLICATION


Can be built in on any green roof with a slope of 5% the most, or on loaded flat roofs. Growth medium as load or other filled weight is needed 80 kg/ m.

## SPECIFICATION

## TECHNICAL DATA

Height: (cm)	50 (Single post:FH-30)
Width: (m)	5 (Force distributed membrane: FGT-180)
Width: (mm)	1000 (Equilibrium table: FGS-1.0)
Length: (m)	50 (Force distributed membrane: FGT-180)
Lenght: (mm)	1200 (Equilibrium table: FGS-1.0)
Thickness: (mm)	10 (Equilibrium table: FGS-1.0)
Diameter: (cm)	ø25 (Single post:FH-30 Supporting area)
Diameter: (mm)	9 (Fastening and lightning conductor cable: FLG-50)
Diameter: (mm)	9,5 (Threaded clamp:FGBK)
Tensile strength weft: (KN/m)	11,5 (Force distributed membrane: FGT-180)
Tensile strength warp: (KN/m)	11,5 (Force distributed membrane: FGT-180)

Reviewed: 2008-06-19 13:27:56



DIADEM USA, Inc.  
8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062  
info@diademusa.com • www.diademusa.com



Green Up the Roof!