

FLG-30-C line system

130095

Fall arrest system for roofs up to a 5% slope with stainless steel anchor posts that are not mechanically fixed

KEY FEATURES

- Simple installation
- No need to break through roof insulation
- No "heat bridge" developing
- Integrated with lightning conductor system



APPLICATION



Cable ferrule is improper name for the component. My suggestion. Stanley N348-888 National 1/8 Inch Wire Cable Clamp. Designed For Forming An Eye Or Loop On Wire Rope - Base Of Saddles Are Grooved To Form Wire Rope For A Stronger Grip - Visual Pack.

SPECIFICATION

TECHNICAL DATA	
Anchor post material:	Stainless steel
Thickness of Plate: (inch)	3/8"
Damping plate material:	Recycled plastic
Mat waterpermeability: (lxm²xs)	105
Tensile strength warp: (kp / ft)	477
Tensile strength weft: (kp / ft)	477
Locking Head Diameter: (inch)	1"
Locking head material:	Stainless steel
Cable diameter: (inch)	6/16"
Safety cable material:	Aluminium
Cable clamp material:	Stainless steel and cast iron

Reviewed: 2012-07-04 14:02:42



DIADEM USA, Inc.
8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062
info@diademusa.com • www.diademusa.com



Green Up the Roof!