

DiaSafe-Line-System "Multi"

Safety-line fall protection system with multiple anchor points.

#130098



Manual

■ Green up the roof!



Application:

When using DiaSafe-Line-System "Multi", the carabiner of the lanyard is always connected to the steel cable - never directly to the post - allowing freedom of movement for users as the carabiner may move freely between posts without disconnecting and reconnecting the lanyard. This system is able to protect the safety of multiple users at a time, as long as only one person is attached to every second section (one section between two users must be left unused).


Installation instructions:

The installation must be completed by certified DiaSafe® installers, and only they are authorised to issue the operating licence. Steps of installation: 1. After installing the filter or protection geotextile layer, position the system on top in the exact position set out in the producer's plan. 2. Unfold the damping mat without creases (standard unfolded size: 3x3m) 3. Spread the ballasting weight evenly, make sure the weight is sufficient for the surface area of the damping mat. 4. Fix the anchoring cable to each post in turn. 5. Finally, the certified installer completes and attaches the control label as well as the circular validation sticker onto the cone. 6. Register the system at diasafe.com by using the serial number.

Installation Tools:

Measuring tape, 5 mm Allen key

Installation Photos:



Reviewed: 2023-10-31 13:57:02

DIADEM USA, Inc.

8795 SW Tualatin Sherwood Rd #1005, Tualatin, OR 97062
Email: info@diademusa.com; Web: www.diademusa.com